

# Won-Door FireGuard MFW

## Pocket Depth Calculation Chart

### STRAIGHT WALLS\*

Clear Opening Width    Min. Pocket Depth

<i>From:</i>	<i>To:</i>	<i>Single</i>
0'-0"	2'-11"	28"
3'-0"	3'-10"	32"
3'-11"	4'-8"	35"
4'-9"	5'-6"	38"
5'-7"	6'-4"	42"
6'-5"	7'-3"	45"
7'-4"	8'-1"	49"
8'-2"	8'-11"	52"
9'-0"	9'-9"	55"
9'-10"	10'-8"	59"
10'-9"	11'-6"	62"
11'-7"	12'-4"	65"
12'-5"	13'-2"	69"
13'-3"	14'-1"	72"
14'-2"	14'-11"	76"
15'-0"	15'-9"	79"
15'-10"	16'-7"	82"
16'-8"	17'-1"	86"
17'-2"	17'-11"	89"
18'-0"	18'-9"	92"
18'-10"	19'-7"	96"
19'-8"	20'-0"	99"

The above chart is for standard Pocket Mounted Motor assemblies.

**\* NOTE:**

Moveable Fire Walls are limited to a maximum length of 20'-0" and maximum height of 9'-0". They are not available in Bi-Parting or Curved configurations.

### OPTIONS EFFECTING POCKET DEPTH:

**Access Control sliding jamb** - Add 1" to pocket depth.

**Pocket cover door and frame** - Above chart allows for a 2" thick cover door. Add appropriate amount if cover door and finish materials are thicker than 2".  
(See pg. 4-10)